

# India Forest Services 2021

## Mechanical Engineering Paper I

**Time Allowed: Three Hours**

**Maximum Marks: 200**

### Question Paper Specific Instructions

**Please read each of the following instructions carefully before attempting questions:**

There are **EIGHT** questions in all, out of which **FIVE** are to be attempted.

Questions no. **1** and **5** are **compulsory**. Out of the remaining **SIX** questions, **THREE** are to be attempted selecting at least **ONE** question from each of the two Sections A and B.

Attempts of questions shall be counted in sequential order. Unless struck off, attempt of a question shall be counted even if attempted partly. Any page or portion of the page left blank in the Question-cum-Answer Booklet must be clearly struck off.

All questions carry equal marks. The number of marks carried by a question/part is indicated against it.


Unless otherwise mentioned, symbols and notations have their usual standard meanings. Assume suitable data, if necessary and indicate the same clearly.

Neat sketch may be drawn, wherever required.


Answers must be written in **ENGLISH** only.

### SECTION A

- Q1.** (a) The Porter governor has equal arms each 300 mm long and pivoted on the axis of rotation. Each ball has a mass of 5 kg and the mass of the sleeve is 20 kg. The radius of rotation of the ball is 150 mm when the governor begins to lift and 200 mm when the governor is at maximum speed. Find the range of speed of the governor. 8
- (b) A U tube open to atmosphere at both ends contains a column length  $l$  of a certain liquid. Find the natural frequency of oscillation of the liquid column. 8



- (c) A member formed by connecting a steel bar to an aluminium bar is shown in the figure below. Calculate the magnitude of the force  $P$  that will cause the total length of the bar to decrease by 0.5 mm. The Young's modulus for steel and aluminium are  $2 \times 10^5$  MPa and  $7 \times 10^4$  MPa respectively. The cross-sectional area of the steel bar is  $25 \text{ cm}^2$  and of the aluminium bar is  $100 \text{ cm}^2$ . 8



- (d) Enlist the different Bravais crystal systems. Also write the relationship between their primitives and between their angles. 8
- (e) Determine the Miller indices of a set of parallel planes, which create intercepts in the ratio of  $2a : 3b$  and parallel to the  $z$ -axis. Consider the lattice to be cubic with  $a = b = c = 4\text{Å}$ . Calculate the interplanar spacing of the planes. 8
- Q2.** (a) (i) A beam is simply supported and carries a uniformly distributed load of 50 kN/m run over the whole span. The section of the beam is rectangular having depth as 500 mm. If the maximum stress in the beam material is  $150\text{ N/mm}^2$  and moment of inertia of the section is  $7 \times 10^8\text{ mm}^4$ , find the span of the beam. 10
- (ii) Draw stress-strain curve for a ductile material and mention salient points on the curve. 5
- (b) A solid circular shaft transmits 100 kW power at 500 rpm. Calculate the shaft diameter, if the twist in the shaft is not to exceed  $1^\circ$  in 2 m length of the shaft, and shear stress is limited to  $75\text{ N/mm}^2$ . Take modulus of rigidity =  $1 \times 10^5\text{ N/mm}^2$ . 15
- (c) Classify the point defects of a crystal structure and define each point defect with the help of suitable diagram. 10
- Q3.** (a)  $A, B, C$  and  $D$  are four masses carried by a rotating shaft at radii 100, 125, 200 and 150 mm respectively. The planes in which masses revolve are spaced 600 mm apart and the masses of  $B, C$  and  $D$  are 10 kg, 5 kg, and 4 kg respectively. Find the required mass  $A$  and the relative angular settings of the four masses so that the shaft shall be in complete balance. 15
- (b) (i) Compare Involute tooth profile with Cycloidal tooth profile of a gear. 7
- (ii) Explain different types of Cams and Followers. 8
- (c) A steel bolt is subjected to a direct pull of 20 kN and transverse shear force of 10 kN. Calculate the diameter of the bolt using maximum principal stress theory and maximum shear stress theory. Take yield point stress for steel as 250 MPa and factor of safety as 2. 10
- Q4.** (a) What is Gibbs Phase Rule? Define liquidus and solidus temperature of a phase diagram. Draw the phase diagram of a Copper-Nickel system. 15
- (b) (i) A beam of rectangular section 200 mm wide and 300 mm deep is simply supported at its ends. It carries a uniformly distributed load of 10 kN/m run over the entire span of 5 m. Taking  $E = 1 \times 10^4\text{ N/mm}^2$ , find the slope at the supports and maximum deflection. 10
- (ii) Derive expression for hoop stress and radial stress in case of a thin cylindrical vessel subjected to only internal pressure. 5
- (c) A rotor having a mass of 10 kg is mounted midway on a 10 mm dia shaft supported at the ends by two bearings. The bearing span is 400 mm. Because of manufacturing defects, the C.G of the disc is 0.20 mm away from the geometric centre. If the system rotates at 3000 rpm, find the amplitude of steady state vibrations and the dynamic force transmitted to each bearing. Take  $E = 2 \times 10^5\text{ MPa}$ . 10

**SECTION B**

**Q5.** (a) A fixture costing Rs. 6,000 is used on shaping machine to perform an operation on a mild steel workpiece. The yearly cost of set-up is Rs. 800. The financial outlay on the money invested is, an interest at 7%, taxes and insurance at 6%, depreciation at 40% and repair at 8%. Further, a profit of 11% is desired on the money invested. Calculate the number of pieces to be manufactured in a year to earn the desired profit. The use of the fixture resulted in labour saving per piece, of Rs. 2.00 and overhead saving is 45% of labour saved. 8

(b) A turning operation is performed on a cylindrical workpiece using the following two tools:  
 (i) HSS tool with nose radius of 0.6 mm.  
 (ii) Carbide tool without nose radius, the side cutting and end cutting angles are 25° and 5° respectively.

If the feed is 0.15 mm in both cases, calculate the maximum height of roughness obtained with HSS tool and Carbide tool. 8

(c) Define the term Value. Explain different types of values. What do you mean by Value Analysis? 8

(d) The General Machine Company buys 9000 units of a particular item from ABC Company. The ordering cost is Rs. 120.00 and the carrying cost is 25% of the unit price. The discount price structure is as follows:

Order Quantity	Price per unit (P)
1 to 99	Rs. 80.00
100 to 499	Rs. 70.00
500+	Rs. 60.00

Assuming instantaneous delivery, find (a) Economic Order Quantity (EOQ); (b) Optimum Total Cost (TC). 8

(e) Explain the following terms with respect to 'C programming language: 8  
 (i) Functions, (ii) Arguments, (iii) Declarations.

**Q6.** (a) An orthogonal turning operation is carried out on a mild steel cylindrical workpiece using an HSS single point cutting tool having rake angle 12° with cutting speed of 250 m/min and feed rate of 0.15 mm/rev. The depth of cut is 1.5 mm and chip thickness ratio is 0.25. If the horizontal cutting force is 700 N and vertical force is 1250 N, determine the following using the Merchant's theory: 15

- (i) Shear strain,
- (ii) Work done by friction,
- (iii) Work done by shear,
- (iv) Total work done,
- (v) Mean shear stress in shear plane.

(b) Consider the following sales data:

Period	1	2	3	4
Sales	350	360	340	405

- (i) Compute the exponent smoothing values for the above data using  $\alpha = 0.1, 0.3$  and  $0.5$ ; and find the respective forecasts for the fifth period.
- (ii) Which ' $\alpha$ ' has the lowest MAD (Mean Absolute Deviation)? 15

- (c) Write 'C' program to find the product of two integers and print the result. 10

- Q7.** (a) During a turning operation on a Lathe machine, if

$D$  = Diameter of cylindrical workpiece (mm)

$L$  = Length of workpiece (mm)

$V$  = Cutting speed (m/min)

$T_L$  = Tool life (min)

$f$  = Feed rate (mm/rev)

$t_m$  = Time to machine per piece (min)

$K_1$  = Direct labour and overhead cost (Rs./min)

$K_2$  = Tool resharpening (regrinding) cost Rs./Piece

TCT = Tool changing time (min) then prove that

- (i) Optimum cutting speed for minimum cost is

$$V_{\text{opt}} = \frac{C}{\left[ \left( \frac{1}{n} - 1 \right) \left( \text{TCT} + \frac{K_2}{K_1} \right) \right]^n}$$

and

- (ii) Corresponding optimum tool life is

$$T_{L(\text{opt})} = \left( \frac{1}{n} - 1 \right) \left( \text{TCT} + \frac{K_2}{K_1} \right)$$

where  $n$  and  $C$  are Taylor's tool life equation constants. 15

- (b) Solve the following sequencing problem and find total elapsed time. The operation time is given in minutes. 15

Machines ↓	Jobs →					
	1	2	3	4	5	6
Machine A	8	10	11	12	16	20
Machine B	7	15	10	14	13	9

- (c) The time study of a machinery operation recorded the cycle time as shown below. The workers were rated at 100%, 80% and 110%. The firm uses a 0.15 percent allowance fraction.

Cycle Time (in minutes)	Number of Times Observed
30	1
34	3
35	4
36	3
41	2

Determine the standard time by using all the three levels of Worker's rating. What is your interpretation of the results so obtained? 10

- Q8.** (a) A rectangular hole of dimensions 10 mm × 15 mm is made by electro discharge drilling in medium carbon steel plate of 6 mm thickness. The supply voltage is 220 volts and the gap is maintained in such a way that discharge takes place at 170 volts. If the resistance and the capacitance in the relaxation circuit are 45 ohm and 10 μF, respectively, determine the time required to drill that hole through the complete thickness of plate. 15

- (b) Find the initial basic feasible solution of the following transportation problem using Vogel's Approximation Method: 15

	$W_1$	$W_2$	$W_3$	$W_4$	Factory Capacity (C)
$F_1$	30	25	40	20	100
$F_2$	29	26	35	40	250
$F_3$	31	33	37	30	150
Warehouse Requirement (R)	90	160	200	50	

- (c) Four different jobs are to be done on four different machines. The set-up and production times are prohibitively high for changeover. Following table indicates the cost of producing job 'i' on machine 'j' in rupees. Assign jobs to different machines so that the total cost is minimized. 10

		Machines			
		1	2	3	4
Jobs	1	5	7	11	6
	2	8	5	9	6
	3	6	7	5	7
	4	10	4	8	3

# Mechanical Engineering Paper II

Time Allowed: Three Hours

Maximum Marks: 200

## Question Paper Specific Instructions

**Please read each of the following instructions carefully before attempting questions:**

There are **EIGHT** questions in all, out of which **FIVE** are to be attempted.

Questions no. 1 and 5 are compulsory. Out of the remaining **SIX** questions, **THREE** are to be attempted selecting at least **ONE** question from each of the two Sections A and B.

Attempts of questions shall be counted in sequential order. Unless struck off, attempt of a question shall be counted even if attempted partly. Any page or portion of the page left blank in the Question-cum-Answer Booklet must be clearly struck off.

All questions carry equal marks. The number of marks carried by a question is indicated against it.

Unless otherwise mentioned, symbols and notations have their usual standard meanings. Assume suitable data, if necessary and indicate the same clearly.

Neat sketch may be drawn, wherever required.

Answers must be written in **ENGLISH** only.

Newton may be converted to kgf using the equality 1 kilonewton (1 kN) = 100 kgf if found necessary.

All answers should be in SI units.

Take: 1 kcal = 4.187 kJ and 1 kg/cm<sup>2</sup> = 0.98 bar

1 bar = 10<sup>5</sup> pascals

Universal gas constant = 8314.6 J/kmol-K

Psychrometric chart is enclosed.

## SECTION—A

**Q1.** (a) Derive the following Clausius-Clapeyron equations:

$$\frac{dP}{dT} = \frac{h_{fg}}{T(V_g - V_f)}$$

and

$$\frac{dP}{P} = \frac{h_{fg}}{RT^2} dT$$

Also explain the physical significance of these equations. 8

(b) An iron cube at a temperature of 400°C is dropped into an insulated bath containing 10 kg water at 25°C. The water finally reaches a temperature of 50°C at steady state. Given that the specific heat of water is 4186 J/kg K. Find the entropy changes for the iron cube and the water. Is the process reversible or irreversible? (Take 0°C as datum) 8

(c) A 12-cylinder, two-stroke cycle CI engine produces 2440 kW of brake power at 550 rpm using stoichiometric light diesel. The engine has bore of 24 cm, stroke of 32 cm, volumetric efficiency of 97%, mechanical efficiency of 88%, combustion efficiency of 98% and air-fuel ratio of 14.5. Calculate the mass flow rate of fuel entering into the engine, brake specific fuel consumption, indicated specific fuel consumption and specific emissions of hydrocarbons due to unburned fuel. [Take density of air  $\rho_a = 1.181$  kg/m<sup>3</sup> and  $R =$  gas constant for air = 0.287 kJ/kg K] 8

- (d) What are the various methods for the determination of convection heat transfer coefficient? Explain briefly. 8
- (e) A gray, diffuse opaque surface ( $\alpha = 0.8$ ) is at  $100^\circ\text{C}$  and receives an irradiation of  $1000 \text{ W/m}^2$ . If the surface area is  $0.1 \text{ m}^2$ , calculate,  
 (i) Radiosity of the surface.  
 (ii) Net radiative heat transfer rate from the surface.  
 (iii) Also calculate the above quantities, if the surface is black.  
 Take  $\sigma = 5.67 \times 10^{-8} \text{ W/m}^2 \text{ K}^4$ . 8
- Q2.** (a) Oil is being cooled by water in a tube-in-tube parallel flow type heat exchanger. The water enters the inner tube at  $15^\circ\text{C}$  and is heated to  $50^\circ\text{C}$ . The oil flows in the annulus and is cooled from  $130^\circ\text{C}$  to  $60^\circ\text{C}$ . Calculate :  
 (i) Exit temperature of each of the fluids, if the existing heat exchanger is operated as a counter flow heat exchanger,  
 (ii) The minimum temperature to which oil may be cooled by increasing the tube length with parallel flow operation, and  
 (iii) The maximum possible effectiveness in parallel flow operation. 15
- (b) A thin hollow stainless steel tube with inner diameter = 7.6 mm and outer diameter = 8 mm is heated with a current of 250 A intensity. The outer surface of the tube is insulated and all the heat generated in the tube wall is transferred through its inner surface. The specific resistance and thermal conductivity of steel are  $0.85 \mu\Omega\text{m}$  and  $18.6 \text{ W/mK}$  respectively. Calculate:  
 (i) Volumetric rate of heat generation in the tube, and  
 (ii) Temperature drop across the wall. 15
- (c) Why does a nonquasi-equilibrium expansion process deliver less work than the corresponding quasi-equilibrium one?  
 A gas of mass 1.5 kg undergoes a quasi-static expansion which follows a relationship :  

$$P = a + b V$$
, where  $a$  and  $b$  are constants.  
 The initial and final pressures are 1000 kPa and 200 kPa respectively and the corresponding volumes are  $0.20 \text{ m}^3$  and  $1.20 \text{ m}^3$ . The specific internal energy of the gas is given by the relation  

$$U = 1.5 PV - 85 \text{ kJ/kg}$$
  
 where  $P$  is in kPa and  $V$  is in  $\text{m}^3/\text{kg}$ . Calculate the net heat transfer and the maximum internal energy of the gas attained during expansion. 10
- Q3.** (a) Mention four points each of advantages and disadvantages of using hydrogen in SI engines. Explain two methods by which hydrogen can be used in CI engines. 15
- (b) What are the reasons for the HC emissions in the exhaust of an automobile? How are catalytic converters helpful in reducing HC, CO and  $\text{NO}_x$  emissions? Why is it good to place a catalytic converter as close to the engine as possible? 15
- (c) A long thin glass-walled, 0.3 cm diameter, mercury thermometer is placed in an air stream with convection coefficient of  $60 \text{ W/m}^2\text{K}$  for measuring transient temperature of air. Consider cylindrical thermometer bulb consists of mercury only, for which  $k = 8.9 \text{ W/mK}$  and

$\alpha = 0.016 \text{ m}^2/\text{h}$ . Calculate the time constant and time required for temperature change to reach half of its initial value. 10

- Q4.** (a) An adiabatic turbine receives a gas ( $C_p = 1.09 \text{ kJ/kg K}$  and  $C_v = 0.838 \text{ kJ/kg K}$ ) at 7 bar and  $1000^\circ\text{C}$  and discharges at 1.5 bar and  $665^\circ\text{C}$ . Determine the Second Law Efficiency and Isentropic Efficiency of the turbine. [Take  $T_0 = 298 \text{ K}$ ] 15
- (b) Using Maxwell's relations and the thermodynamic definition for  $C_p$  and  $C_v$  in terms of gradients, show the following:
- (i) 
$$Tds = C_v dT + T \left( \frac{\partial P}{\partial T} \right)_V dV$$

$$= C_p dT - T \left( \frac{\partial V}{\partial T} \right)_P dP$$
- (ii) Joule-Thomson coefficient
- $$\mu_j = \frac{1}{C_p} \left[ T \left( \frac{\partial V}{\partial T} \right)_P - V \right],$$
- (iii) Also prove that there is no change in temperature when an ideal gas is made to undergo Joule-Thomson expansion. 15
- (c) State the three main advantages of induction swirl. The spark plug is fired at  $18^\circ \text{ bTDC}$  in an engine running at 1800 rpm. It takes  $8^\circ$  of engine rotation to start combustion and get into flame propagation mode. Flame termination occurs at  $12^\circ \text{ aTDC}$ . Bore diameter is 8.4 cm, and the spark plug is offset by 8 mm from the centreline of the cylinder. The flame front can be approximated as a sphere moving out from the spark plug. Calculate the effective flame front speed during flame propagation. 10

### SECTION—B

- Q5.** (a) Mention the different factors to be considered for selecting the site of hydroelectric power plants. 8
- (b) Discuss the various pollutants emitting from a steam power plant. 8
- (c) Distinguish between Turbomachines and Positive Displacement Machines in respect of the following :
- (i) Basic mechanism of energy transfer,
- (ii) Features of applications, and
- (iii) Features of mechanical construction. 8
- (d) What is an Economiser? Mention the advantages gained by using Economisers in a modern power plant. 8
- (e) Explain the psychrometric process of steam injection. Give its applications. 8
- Q6.** (a) Distinguish among Fans, Blowers and Compressors. A compressor draws air from the atmosphere at 1.5 bar and 300 K at a velocity of 80 m/s. The isentropic efficiency of the compressor is 70%. The stagnation pressure ratio is 3.2. Find the stagnation pressure at the exit and the power of the driving motor if the mechanical efficiency is 90% for a flow rate of 30 kg/minute. 15



Take for air  $\gamma = 1.4$ .  $C_p = 1.004$  kJ/kg K

- (b) It is required to design an air-conditioning system for an industrial process for the following conditions:

Outdoor conditions: 32°C DBT and 65% RH

Inside design conditions : 25°C DBT and 60% RH

Volume flow rate of outside air : 195 m<sup>3</sup>/min

Coil ADP : 13°C

The required condition is achieved by first cooling and dehumidifying the outside air and then by heating.

Calculate the following:

- (i) The cooling capacity of the cooling coil and its bypass factor.
- (ii) Heating capacity of the heating coil in kW and surface temperature of the heating coil if its bypass factor is 0.35.
- (iii) The mass of water vapour removed per hour. Show all processes on a psychrometric chart along with a schematic diagram to carry out the above processes. 15

(Psychrometric chart is attached)

- (c) Explain the effect of increase in condenser temperature on the performance of vapour compression system. Draw *T-S* and *P-h* diagrams also. 10

- Q7.** (a) A single cylinder, single acting compressor having bore and stroke of 16 cm and 24 cm respectively runs at a speed of 120 rpm and the indicated mean effective pressure is 2.2 bar. The pressure limits of the refrigeration system operating on ammonia are 9.74 bar and 2.47 bar and the temperatures of refrigerant at entry to and exit from condenser are 40°C and 17°C respectively. The cooling water flow across the condenser is 15.45 kg/min and inlet and outlet temperatures of cooling water are 16°C and 24°C respectively. The mass of ice produced per hour from water at 20°C is 56 kg. Assume the latent heat of ice as 335 kJ/kg. Calculate the following:

- (i) Compressor power in kW.
- (ii) Mass flow rate of ammonia/min.
- (iii) Coefficient of performance.
- (iv) Dryness fraction of ammonia entering the compressor.

The relevant properties of ammonia are given in the table:

Pressure, P (bar)	Saturation Temperature, $T_s$ (°C)	Enthalpy ( <i>h</i> ), (kJ/kg)		Specific heat $C_p$ , (kJ/kg K)	
		Liquid	Vapour	Liquid	Vapour
9.74	24	312.87	1482.53	4.61	2.87
2.47	-14	135.82	1445.2	—	—

Take *C* for water as 4.1868 kJ/kg K.

Draw *T-S* and *P-h* diagrams also. The state of ammonia is wet vapour at entry to compressor as mentioned in (iv). If the state of ammonia at entry to compressor is either dry saturated or superheated, then comment what will happen to COP and why. 20

- (b) Explain Load Curves. Distinguish between Base Load and Peak Load power plants. 10

- (c) For a single stage compressor, the pressure, temperature and velocity of air at the inlet are 120 kPa, 300 K and 12 m/s, respectively. The values of the pressure, temperature and velocity at the exit are 220 kPa, 380 K and 90 m/s, respectively. The exit is 2 m above the inlet. Determine,

- (i) Actual work,  
(ii) Isentropic work, and  
(iii) Efficiency of the compressor.

10

For air, take

$$\gamma = 1.4.$$

$$C_p = 1.004 \text{ kJ/kg K}.$$

- Q8.** (a) The following data are related to the design of a single-sided centrifugal compressor :

Power input factor ( $\psi$ ) = 1.02

Slip factor ( $\sigma$ ) = 0.8

Rotational speed ( $N$ ) = 300 rev/s

Overall diameter of impeller = 0.6 m

Eye-tip diameter = 0.4 m

Eye-root diameter = 0.2 m

Air mass flow ( $m$ ) = 10 kg/s

Inlet stagnation temperature ( $T_{01}$ ) = 300 K

Inlet stagnation pressure ( $P_{01}$ ) = 1.1 bar

Isentropic efficiency ( $\eta_i$ ) = 77%

Density of air ( $\rho_a$ ) = 1.185 kg/m<sup>3</sup>

Effective efficiency of compression ( $\eta_{ec}$ ) = 88%

$R_{\text{air}} = 0.287 \text{ kJ/kg K}$ ,  $C_p$  (air) = 1.005 kJ/kg K

Take  $(\gamma/\gamma - 1)_{\text{air}} = 3.5$  and  $C_{r2} = C_{a1}$ .

Determine,

- (i) Pressure ratio of the compressor and the power required to drive it, assuming that the velocity of the air at inlet is axial,

- (ii) Inlet angle of the impeller vanes at root and tip radii of the eye, assuming that the axial inlet velocity is constant across the eye annulus, and

- (iii) Axial depth of the impeller channels at the periphery of the impeller.

20

- (b) A water turbine of runner diameter 1.2 m works with a head of 112 m of water, 5 m<sup>3</sup>/sec of flow and produces a power of 2700 kW at a speed of 400 rpm. A one-fourth size model of the water turbine is required to be tested in a laboratory. The maximum head available in the laboratory is 8 m of water. Determine,

- (i) the flow rate required to be planned,  
(ii) the speed at which the model is to be tested, and  
(iii) the output of the model.

10

- (c) Give the mass balance of a steam generator.

10